



GUARDIANDOORS.COM

0800 783 6602

ROLLER SHUTTERS - SECTIONAL OVERHEAD DOORS - INSULATED DOORS - FOLDING DOORS  
STEEL DOORS - FIRE RATED DOORS - SECURITY DOORS - SLIDING GATES - HIGH SPEED DOORS

## ARES Security Tested Roller Shutters Certified to LPS 1175 Issue 7, Security Rating 4 (SR4)

### ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- LPCB ref. 1396 LPS 1175: Issue 7 Cert. No. 1396a
- Certified to LPS 1175 Issue 7, Security Rating 4 (SR4)
- Secured by Design Police Preferred Specification

### TYPICAL APPLICATIONS

#### Suitable applications include:

- Laboratories, Research and Data Storage Facilities
- Critical National Infrastructure
- Cash and Valuables in Transit
- Government and Defense

### SELF-LOCKING TECHNOLOGY

- No auxiliary locking required - manual or electronic
- Unique profiles lock the shutter in any stop position - fully closed or not
- Allows external first point of entry through the shutter

### OPTIONS

- Polyester powder coated to any standard RAL /BS colour
- High or low duty cycle electrical motors
- Internal and External installations complete with sub assembly steel frames as required
- Variable reinforced core to protect against specific attack methodology

### SUBSTRATE

#### Certified installation onto:

- Blockwork
- Concrete
- Structural Steelwork
- Sub assembly steel framework



Guardian Industrial Doors Ltd  
Managing Director: RW Everitt Company Secretary: E Everitt  
Registered Office: 45 Progress Road, Leigh on Sea, Essex SS9 5PR  
Fax No 01702 260117  
Registered in England No 1447746



GUARDIANDOORS.COM

0800 783 6602

ROLLER SHUTTERS - SECTIONAL OVERHEAD DOORS - INSULATED DOORS - FOLDING DOORS  
STEEL DOORS - FIRE RATED DOORS - SECURITY DOORS - SLIDING GATES - HIGH SPEED DOORS

## APPROVED DIMENSIONS

### External Face Fit

Maximum certified width: 6000mm

Minimum certified width: 1000mm

Maximum certified height: 10,000mm

Minimum certified height: 1800mm

### Internal Face Fit

Maximum certified width: 6000mm

Minimum certified width: 1000mm

Maximum certified height: 10,000mm

Minimum certified height: 1000mm

## SHUTTER CURTAIN

Extruded aluminium self-locking profiles with reinforced cores

Finish as delivered: polyester powder coated in standard RAL/BS colour

## OPERATION

Motorised to allow controlled ascent and descent Tube Motor - Low duty cycle, or where limited to single phase supply

External Drive Motor - High duty cycle or for larger apertures

## BOTTOM RAIL

Reinforced extruded aluminium section with strengthened core

Finish as delivered: polyester powder coated in standard RAL/BS colour

## FRAMES/GUIDES

Heavy duty extruded aluminium guide profiles anchored direct to the structure

Finish as delivered: polyester powder coated in standard RAL/BS colour

## CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or possible to integrate into building management systems and third party alarms

Safety on close as assessment directs

High duty cycle motor and battery backup options



Guardian Industrial Doors Ltd  
Managing Director: RW Everitt Company Secretary: E Everitt  
Registered Office: 45 Progress Road, Leigh on Sea, Essex SS9 5PR  
Fax No 01702 260117  
Registered in England No 1447746