



GUARDIANDOORS.COM 0800 783 6602

ROLLER SHUTTERS - SECTIONAL OVERHEAD DOORS - INSULATED DOORS - FOLDING DOORS STEEL DOORS - FIRE RATED DOORS - SECURITY DOORS - SLIDING GATES - HIGH SPEED DOORS

SR2

LPS 1175 CERTIFIED BOLT-ON SECURITY SHUTTERS

ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB) LPCB ref. 1396 LPS 1175:
- Certified to LPS 1175 Issue 7, Security Rating 4 (SR2)
- Secured by Design Police Preferred Specification

TYPICAL APPLICATIONS

Suitable applications include:

- Medium risk commercial buildings
- Public facilities schools, universities, community centres
- Retail outlets point of sale gantries
- Cultural Buildings

SELF-LOCKING TECHNOLOGY

- No auxiliary locking required manual or electronic
- Unique profiles lock the shutter in any stop position fully closed or not
- Allows external first point of entry through the shutter

OPTIONS

- Polyester powder coated to any standard RAL /BS colour
- High or low duty cycle electrical motors
- Can be partially or fully perforated to maintain airflow without compromising security
- Internal and External installations complete with sub assembly steel frames as required

SUBSTRATE

Certified installation onto:

Brickwork

Blockwork

Concrete

Structural Steelwork

Sub assembly steel framework

APPROVED DIMENSIONS

Maximum certified width: 8000mm Minimum certified width: 1000mm Maximum certified height: 10,000mm Minimum certified height: 2000mm

SHUTTER CURTAIN

Extruded aluminium self-locking profiles

Finish as delivered: polyester powder coated in standard RAL/BS colour

Option to fully or partially perforate



















GUARDIANDOORS,COM 0800 783 6602

ROLLER SHUTTERS - SECTIONAL OVERHEAD DOORS - INSULATED DOORS - FOLDING DOORS STEEL DOORS - FIRE RATED DOORS - SECURITY DOORS - SLIDING GATES - HIGH SPEED DOORS

SR2 LPS 1175 CERTIFIED BOLT-ON SECURITY SHUTTERS

OPERATION

Motorised to allow controlled ascent and descent

Tube Motor - Low duty cycle, or where limited to single phase supply

External Drive Motor - High duty cycle or for larger apertures



Reinforced extruded aluminium section with strengthened core

Finish as delivered: polyester powder coated in standard RAL/BS colour



FRAMES/GUIDES

Heavy duty extruded aluminium guide profiles anchored direct to the structure

Finish as delivered: polyester powder coated in standard RAL/BS colour

CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or possible to integrate into building management systems and third party alarms

Safety on close as assessment directs

High duty cycle motor and battery backup options









